

# Series GX15 Pneumatic Pump



## PUMP CATEGORY

Type: Plunger  
Control: Cycle Speed  
Stroke: 1 in (25 mm) Fixed

## FLOW RATE

0.04 - 1.46 USG/H (0.15 - 5.53 L/H)

## PRESSURE

0 - 3,500 PSIG (0 - 241.32 BARG)

## SUPERIOR DESIGN

- Durable, High-Quality Materials
- No Springs or Diaphragms
- Accurate and Repeatable Injection
- Quick Maintenance and Low Downtime
- Optimized for Shale Oil and Gas Production
- High Return on Investment

## CHEMICAL RESISTANCE

Proprietary, high-quality seal materials enable CheckPoint pumps to provide unparalleled chemical resistance. Wetted components are available in an array of materials. Chemical applications include, but are not limited to:

- Scavengers (H<sub>2</sub>S, O<sub>2</sub>, CO<sub>2</sub>)
- Hydrate Inhibitors (MeOH, MEG, LDHI)
- Foamers and Defoamers
- Corrosion, Scale, and Paraffin Inhibitors
- Clarifiers, Biocides, Bleaches, and Acids

## ZERO EMISSIONS

CheckPoint offers standard integrated gas recovery capable of 120 PSIG (8.3 BARG) exhaust backpressure.

## WARRANTY

CheckPoint guarantees 40 months of material and workmanship.

MODEL	FLOW RATE (MINIMUM) USG/H (L/H)	FLOW RATE (MAXIMUM) USG/H (L/H)	WORKING PRESSURE (MAXIMUM) PSIG (BARG)	PISTON DIAMETER IN (MM)	PLUNGER DIAMETER IN (MM)	DIMENSIONS L X W X H IN (MM)	WEIGHT LB (KG)	SUCTION CONNECTION	DISCHARGE CONNECTION
GX15 1/4"	0.04 (0.15)	1.46 (5.53)	3,500 (241.32)	1.5 (38.10)	1/4 (6.35)	4.75 (121) X 5.47 (139) X 10.6 (269)	8.05 (3.65)	1/4" MNPT	1/4" MNPT

Tabular data should be used for quick reference only. See performance curves for accurate pump selection.



www.cppumps.com • sales@cppumps.com



CheckPoint's positive displacement, reciprocating chemical injection pumps are specifically designed for, and extensively proven in, demanding oil and gas production applications worldwide. Both the design and construction of this pump produce a perfect balance of quality, price, and long-term cost of ownership. The pneumatic motor, composed entirely 316 SS, remains isolated from the wet end and is dependably able to run on pressurized gas or liquid without stalling. CheckPoint's double-acting design eliminates a return spring, which greatly increases repeatability and reliability over time. Our proprietary, integrated speed control offers simple, intuitive, and precise settings.

The **Series GX15** pump delivers up to 1.46 USG/H (5.53 L/H) and can reliably inject into pressures up to 3,500 PSIG (241.32 BARG). Our pumps maintain unparalleled chemical resistance due to the essential integration of high-quality, proprietary seal materials. In order to meet a wide variety of chemical compatibility needs, wetted parts are available in an array of materials, such as 316 SS, Hastelloy C-276, Duplex 2205, Super Duplex 2507, ceramic and titanium, and seals are available in Viton, HNBR, FKM, and FFKM. All construction materials are compatible with sour gas according to NACE MRO175 and ISO 15156.

Only CheckPoint's pneumatic pumps can recover exhaust gas under significant backpressure. This unique gas recovery system enables processes to reuse drive gas after it has powered the pump. Consider the environmental benefits, as well as the cost savings, achieved by rerouting spent drive gas to the suction side of a gas compressor. This exclusive feature aids in lowering gas emissions while powering thermoelectric generators, feeding catalytic heaters, and even running within enclosures while venting externally.

We recommend "Plug & Play" injection packages (as pictured below) as an optimum solution to efficiently and effectively integrate chemical injection into your process. CheckPoint has engineered, manufactured, and sourced high-quality components which, combined in a package with our pumps, maximize product life and optimize productivity. We also offer custom system design and technical services to meet specialty product requirements. CheckPoint will create a solution that meets your specific chemical injection needs, from concept to completion.

